

TECHNICAL DATA  
DATA SHEET 4314, REV. -

## FIXED POSITIVE 3 AMP 5 VOLT LOW DROPOUT VOLTAGE REGULATOR

**FEATURES:**

- ISOLATED HERMETIC PACKAGE
- SIMILAR to INDUSTRY TYPE LT1085-5
- LOW DROP OUT

**MAXIMUM RATINGS**


All ratings are at  $T_C = 25^\circ\text{C}$  unless otherwise specified.

Parameter	Conditions	Maximum	Units
Input Voltage	-	30	Vdc
Junction Operating Temperature Range	-	-55 to +150	$^\circ\text{C}$
Storage Temperature Range	-	-65 to +150	$^\circ\text{C}$
Thermal Resistance	-	2.75	$^\circ\text{C/W}$

**ELECTRICAL CHARACTERISTICS**

Symbol	Parameter	Conditions	Min.	Max.	Units
$V_{REF}$	Reference Voltage	$I_{OUT} = 0 \text{ mA}$ , $T_j = 25^\circ\text{C}$ , $V_{IN} = 8 \text{ V}$ $0 \leq I_{OUT} \leq I_{FULL \text{ LOAD}}$ , $6.5 \text{ V} \leq V_{IN} \leq 30 \text{ V}$	4.96 4.92	5.04 5.08	V
$V_{RLINE}$	Line Regulation	$I_{OUT} = 0 \text{ mA}$ , $T_j = 25^\circ\text{C}$ , $6.5 \text{ V} \leq V_{IN} \leq 20 \text{ V}$ $6.5 \text{ V} \leq V_{IN} \leq 30 \text{ V}$		8 20	mV mV
$V_{RLOAD}$	Load Regulation	$V_{IN} = 8 \text{ V}$ , $0 \leq I_{OUT} \leq I_{FULL \text{ LOAD}}$ , $T_j = 25^\circ\text{C}$		20	mV
$V_{DO}$	Dropout Voltage	$\Delta V_{OUT} = 50 \text{ mV}$ , $I_{OUT} = I_{FULL \text{ LOAD}}$		6.5	V
$I_{LIM}$	Current Limit	$V_{IN} = 10 \text{ V}$		4.0	A
$I_Q$	Quiescent Current	$V_{IN} \leq 30 \text{ V}$		10	mA
	Thermal Regulation	$T_A = 25^\circ\text{C}$ , 30 ms pulse		0.02	%/W
	Long Term Stability	$T_A = 125^\circ\text{C}$ , 1000 Hrs.		1.0	%

## SENSITRON

**TECHNICAL DATA**  
**DATA SHEET 4314, REV. -**
**MECHANICAL DIMENSIONS: In inches / mm**

**TO-258**
**PINOUT TABLE**

TYPE	PIN 1	PIN 2	PIN 3
TO-258, 5V Regulator	GND	VOUT	VIN

**DISCLAIMER:**

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the Sensitron Semiconductor sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall Sensitron Semiconductor be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). Sensitron Semiconductor assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall Sensitron Semiconductor be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or Sensitron Semiconductor.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of Sensitron Semiconductor.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.