

HERMETIC ULTRAFAST SOFT RECOVERY RECTIFIER

Features:

- Low forward voltage drop
- Low power loss, high efficiency
- Very high surge capacity
- Soft reverse recovery at low and high temperature
- Trr guaranteed lower than 40 nsec
- Electrically / mechanically stable during and after packaging

Maximum Ratings:

Characteristics	Symbol	Condition	Max.	Units
Peak Inverse Voltage	V_{RWM}	-	300	V
Max. Average Forward Current	$I_{F(AV)}$	50% duty cycle, rectangular wave form, $T_C = 65\text{ }^\circ\text{C}$	25	A
Max. Peak One Cycle Non-Repetitive Surge Current	I_{FSM}	8.3 msec, sine pulse	300	A
Thermal Impedance	Z_{TH}	$T_C = 25\text{ }^\circ\text{C}$	1.3	$^\circ\text{C} / \text{W}$
Max. Junction Temperature	T_J	-	- 65 to + 150	$^\circ\text{C}$
Max. Storage Temperature	T_{stg}	-	- 65 to + 150	$^\circ\text{C}$

Electrical Characteristics:



Characteristics	Symbol	Condition	Typ.	Max.	Units
Max. Forward Voltage Drop	V_{F1}	@ 10A, Pulse, $T_J = 25\text{ }^\circ\text{C}$ @ 25A, Pulse, $T_J = 25\text{ }^\circ\text{C}$	0.92 1.02	0.99 1.12	V
	V_{F2}	@ 10A, Pulse, $T_J = 125\text{ }^\circ\text{C}$ @ 25A, Pulse, $T_J = 125\text{ }^\circ\text{C}$	- -	0.92 1.05	V
Max. Reverse Current	I_{R1}	@ $V_R = 300\text{V}$, Pulse, $T_J = 25\text{ }^\circ\text{C}$	2	30	μA
	I_{R2}	@ $V_R = 300\text{V}$, Pulse, $T_J = 125\text{ }^\circ\text{C}$	-	500	μA
Reverse Recovery Time	t_{RR}	$I_F = 0.5\text{A}$; $I_R = 1.0\text{A}$, $I_{RM} = 0.25\text{A}$ $T_J = 25\text{ }^\circ\text{C}$	35	40	nsec
Max. Junction Capacitance	C_T	@ $V_R = 10\text{V}$, $T_C = 25\text{ }^\circ\text{C}$ $f_{SIG} = 1\text{MHz}$, $I_{SIG} = 100\text{mV (p-p)}$	100	-	pF

SENSITRON
TECHNICAL DATA
DATA SHEET 6083 REV C



MECHANICAL DIMENSIONS: In Inches / mm

*Dimensions shown are with solder dipping

SHD-3 HIGH PROFILE



SHD-3B HIGH PROFILE



PINOUT TABLE:

TYPE	PIN 1 (Base)	PIN 2
SINGLE RECTIFIER in a Surface Mount Package	CATHODE	ANODE

SENSITRON
TECHNICAL DATA
DATA SHEET 6083 REV C

PART ORDERING INFORMATION:

SHD374914BXX X

Part Number

Package
Blank (SHD-3)
B= SHD-3B

Screening Level (blank is no screening):

Suffix	Screened in Accordance with:
blank	No screening level
S	MIL-PRF-19500, TXV Level
SS	MIL-PRF-19500, S Level

QCI (blank is no QCI):

Suffix	Inspection in Accordance with:
blank	No QCI
Q	MIL-PRF-19500 QCI

DISCLAIMER:

1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the Sensitron Semiconductor sales department for the latest version of the datasheet(s).

2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.

3- In no event Sensitron Semiconductor be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). Sensitron Semiconductor assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.

4- In no event shall Sensitron Semiconductor be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.

5- No license is granted by the datasheet(s) under any patents or other rights of any third party or Sensitron Semiconductor.

6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of Sensitron Semiconductor.

7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.